



Ceiling Installation

Please read all instructions prior to installation.

Successful installation of the Ceiling does require placing each section in the elevator in proper sequence as described below. Keep all sections folded until they are placed inside the elevator cab. All components are customized for a specific elevator and individually labeled. **Many components are labeled for the “left” and “right” side of the cab. Your orientation for the left and right side will be when you are inside the cab facing the lobby entrance (see Elevator Cab Configuration on Page 2).**

Step 1 Ceiling

- A. Place the Ceiling Panel inside the elevator while still folded. Unfold the Ceiling Panel and position it against the cab ceiling.
- B. To install or de-install the Ceiling Panel extend the Support Pole and position it along the center fold to temporarily hold the Ceiling Panel in place.

Step 2 Ceiling Supports

Prior to installing the Cab Liner, slide the Ceiling Supports onto the top edge of the Cab Liner panels. In order to secure the Ceiling Panel, place three supports on each wall making sure to cover panel seams.

No ceiling supports will be provided for “non-split walls with handrails covered.”


Step 3 Cab Liner

- A. Verify that the Ceiling is still centered on the ceiling lights.
- B. Hold the Ceiling Panel tight against the cab ceiling with the Support Pole. Install the Cab Liner as per the enclosed installation instructions.
- C. Lower the Ceiling Panel into place.

Removal of Ceiling

To remove the Ceiling Panel, first install the Support Pole as in Step 1-B. Remove the Cab Liner in reverse order of the instructions to install, remove Support Pole, lower the Ceiling Panel and remove from the cab.

Elevator Cab Configuration



NOTE: Each Door Guard Ceiling is fabricated to the exact cab dimensions and configuration of the elevator for which it was intended. This Ceiling can only be used in elevators with the exact same model configuration and dimensions. Do not attempt to use your Ceiling in an elevator using a different dimensional "foot print" as it will not protect the elevator interior as intended and you may damage your Ceiling.

We strongly recommend storage of your panels in a vertical or horizontal position. TO PREVENT BOWING, DO NOT LEAN PANELS AGAINST WALLS. Panels should be stored at temperatures between 60 and 80 degrees Fahrenheit.

WARRANTY

One (1) year manufacturer's warranty indicating both cab liner and door liner is free of defects in material and workmanship. Warranty will not cover normal wear and tear, damage incurred during transportation, installation, de-installation, nor Locking Plate compression exceeding 70 pounds, or if not stored in accordance with manufacturer's recommendations as described in all installation instruction sheets. Unauthorized modifications will nullify the warranty.

**Door Guard Inc., Pittsburgh, PA 15205
Phone 724 695 8936, Fax 724 695 8937
email: sales@doorguardinc.com
Website: www.doorguardinc.com
U.S. Patent 61366251**